


<b>PIC Wire &amp; Cable</b>	<b>Connector Specification</b>	<b>120611</b>
A Division of the Angelus Corporation Ph (262) 246-0500 Fax (262) 246-0450 www.picwire.com N220 W1051 Springdale Road, Waukesha, WI 53186	Approved: <i>JMS</i>	Date 11/17/10
	Distribution : USER	Rev. 2 (07/21/22) Uncontrolled Document

**N 90° Plug**  
for S28110 & HH85295F Cables



*Features Not Shown : Safety Wire Holes, Gasket in Front*

**PERFORMANCE**

Nominal Impedance	50 Ohms
Frequency Range	DC - 18 GHz
Temperature Rating	- 65° to + 200° C
Voltage Rating	500 VRMS

**CONNECTOR WEIGHT (Each)**

2.61 ounces (73.94 grams)

**RoHS COMPLIANT**

Complies to RoHS Standards

**INSTALLATION**

Solder-on Termination

**CONSTRUCTION**

**Materials:**

Body	Stainless Steel
Coupling Nut	Stainless Steel
Solder Ferrule	Brass
Center Contacts	Beryllium Copper
Dielectric	PTFE, Ultem
Gasket	Silicon Rubber

**Finish :**

Body, Coupling Nut	Passivated
Solder Ferrule	Gold
Center Contact	Gold

**Applicable Standards**

MIL-STD 348
MIL-C-39012

- Notes :**
- 1) A 2.5" piece of Raychem ATUM heat shrink P/N ATUM-16/4-0 provided with connector for purpose of strain relief & moisture protection.
  - 2) Please refer to T-120611 Termination Instruction sheet for strip dimensions & instructions.